



DECLARATION OF PERFORMANCE

PRODUCT TYPE

Bothwell Castle Red Blend BC2

INTENDED USE OF THE PRODUCT

Facing Masonry, Load bearing or non-load bearing masonry structures including internal linings and partitions for building and civil engineering

NAME AND ADDRESS OF MANUFACTURER

RAEBURN BRICK LIMITED, EAST AVENUE, PRIESTFIELD INDUSTRIAL ESTATE, BLANTYRE, SOUTH
LANARKSHIRE, G72 0JB

SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE OF THE CONSTRUCTION PRODUCT AS SET OUT IN ANNEX V:

SYSTEM 4

Essential Characteristics	Performance		Harmonised Technical Specification
Dimensions & Tolerance mm	215 x 102.5 x 65mm		BS EN 771-1:2011+A1:2015
	Tolerance	T2	
	Range	R2	
Configuration	Vertically Perforated 18-25%		
Compressive Strength (perp to bed face) N/mm2	70		
	Category II		
Dimensional Stability mm/m3	NPD		
Bond Strength fixed N/mm2	0.15		
Active Soluble Salts	S2		
Reaction to Fire	Class A1		Commission decision 2000/605/EC
Water Absorption %	7		BS EN 771-1:2011+A1:2015
Water Vapour Permeability	50/100		
Direct Airborne sound insulation kg/m3	1500		
Thermal Resistance kg/m3	1500		
Durability against freeze thaw	F2		
Dangerous Substances	NPD		

The performance of the product is in conformity with the declared performance. This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

James Raeburn – Managing Director, Raeburn Brick Limited

ISSUE/PRINT DATE: 06 February 2025